

Fiche produits / Product description

TISA-LACE GLASS

FLAT BRAIDED TAPE GLASS FIBRE

-55°C to 427°C

FEATURES AND ASSETS:

- **Flexible**
- **Knot resistance for B C E finishes**
- **Thin wall**
- **Lightweight**

TYPICAL APPLICATION:

- **Military**
- **Aeronautical**
- **Telecom**



DESIGNATION:

Flat braided tape made from continuous filament of glass yarn .

SPEC.:

A-A-52083 (Formerly, MIL-T-43435 Type IV)

NSA8420-7 (LTFV2-9-C)

NSA8420-10 (LTFV2-9-D)

TEMPERATURE:

-55°C to 427°C (-67°F to 800°F)

COLOUR:

Natural (white). Other colors on request.

PACKAGING:

Size 1 & 2, rolls of 250 m

Size 3, 4 & 5, rolls of 500 m

Part Number	Spec. Size	Width (mm)		Thickness (mm)		Strength (min.) (Kg)	Standard rolls (m)
		Min.	Max	Min.	Max		
LTFV1	1	5,16	6,30	0,33	0,48	90,6	250
LTFV2	2	2,51	3,07	0,33	0,48	45,3	250
LTFV3	3	1,96	2,39	0,33	0,48	34,0	500
LTFV4	4	1,37	1,68	0,33	0,48	22,7	500
LTFV5	5	1,14	1,40	0,33	0,48	-	500

FINISH:

- A Natural (uncoated)
- C Synthetic Elastomer Rubber
- D TFE-Floracarbon coating
- E Vinyl Chloride or vinyl chloride acetate copolymer

ORDERING CODE:

Ordering code: ex: LTFV3-9-C (Size 3, white, finish C)

