

Fiche produits / Product description

TISA-LACE GLASS/PTFE

BRAIDED CORD GLASS FIBRE

-55°C to 427°C

FEATURES AND ASSETS:

- **Flexible**
- **Knot resistance for D finish**
- **Lightweight**

TYPICAL APPLICATIONS:

- **Military**
- **Aerospace**
- **Telecom**

**DESIGNATION:**

Braided cord made from continuous filament of glass yarn coated with PTFE.

STANDARDS:

DAN107-1

DAN107-2

TEMPERATURE:

-55°C to 427°C (-67°F to 800°F)

COLOUR:

Natural (white). Other colors on request.

PACKAGING:

Size 1.1, rolls of 500 m

Size 2.0, rolls of 100 m

Part Number	Spec. Size	Nominal diam. (mm)	Strength (min.) (Kg)	Standard rolls (m)
LCFV1.1	1.1	1.1	30	500
LCFV2.0	2.0	2.0	95	100

FINISH:

D TFE-Fluorocarbon coating

ORDERING CODE:

Ordering code example : LCFV1.1-9-D/500 (Size 1.1, white, finish D, 500m)

The information and illustrations given herein are believed to be reliable. Tresse-Industrie makes no warranties as to their accuracy or completeness and disclaims any liability in connection with their use. Tresse-Industrie's only obligations are those in the standard terms of sale for this product and Tresse-Industrie will not be liable for any consequential or other damages arising out of the use or misuse of this product. Users should make their own evaluation to determine the suitability of the product for specific applications.

