

Fiche produits / Product description

TISA-LACE NOMEX®

FLAT BRAIDED TAPE NOMEX®

-55°C to 260°C

FEATURES AND ASSETS:

- **Nomex® Lacing tape**
- **Thin wall**
- **Lightweight**

TYPICAL APPLICATION:

- **Military**
- **Aeronautical**
- **Telecom**

DESIGNATION:

Flat braided tape made from continuous filament of aramid Nomex®

SPEC.:

A-A-52084 (Formerly, MIL-T-43435 Type V)

TEMPERATURE:

-55°C to +260°C (-67°F to 500°F)

COLOUR:

White with Green tracer. Other colors on request.

PACKAGING:

Size 1 & 2, rolls of 250 m

Size 3 & 4, rolls of 500 m

Part Number	Spec. Size	Width (mm)		Thickness (mm)		Strength (min.) (Kg)	Standard rolls (m)
		Min.	Max	Min.	Max		
LTNX1	1	4,57	5,59	0,33	0,48	38,6	250
LTNX2	2	2,51	3,07	0,28	0,43	23,7	250
LTNX3	3	1,73	2,11	0,23	0,38	15,9	500
LTNX4	4	1,27	1,55	0,18	0,33	11,3	500

FINISH:

- A Natural (uncoated)
- B Microcrystalline Fungicide Wax
- C Synthetic Elastomer Rubber

ORDERING CODE:

ex: LTNX2-9-B (size 2, white, finish B)



NOMEX-07-2015-B