

Fiche produits / Product description

TISA-LACE NYLON

FLAT BRAIDED TAPE NYLON

-55°C to 121°C

FEATURES AND ASSETS:

- **Flexible**
- **Knot resistance for B C E finishes**
- **Thin wall**
- **Lightweight**

TYPICAL APPLICATION:

- **Military**
- **Aeronautical**
- **Telecom**



DESIGNATION:

Flat braided tape made from continuous filament of high tenacity Polyamide 6-6 Nylon

SPEC.:

A-A-52080 (Formerly, MIL-T-43435 Type I)

NSA8420-3 (LTNY3-9-B)

TEMPERATURE:

-55°C to 121°C (-67°F to 250°F)

COLOUR:

Natural (white) or Black. Other colors on request.

PACKAGING:

Size 1, 2, rolls of 250 m

Size 3, 4, 5, 6 rolls of 500 m

Part Number	Spec. Size	Width (mm)		Thickness (mm)		Strength (min.) (Kg)	Standard rolls (m)
		Min.	Max	Min.	Max		
LTNY1	1	4,57	5,59	0,33	0,48	61,2	250
LTNY2	2	2,51	3,07	0,30	0,46	36,3	250
LTNY3	3	1,96	2,39	0,28	0,43	22,7	500
LTNY4	4	1,37	1,68	0,23	0,38	11,3	500
LTNY5	5	1,14	1,40	0,15	0,36	6,8	500
LTNY6*	6	0,78	1,18	0,14	0,18	5,0	500

* Non-listed size in above standards

FINISH:

- A Natural (uncoated)
- B Microcrystalline Fungicide Wax
- C Synthetic Elastomer Rubber
- E Vinyl Chloride or vinyl chloride acetate copolymer

ORDERING CODE:

ex: LTNY3-0-C (Size 3, Black, finish C)



NYLON-08-2015-B