

Fiche produits / Product description

TISA-LACE POLYESTER

FLAT BRAIDED TAPE POLYESTER

-67°C to 177°C

FEATURES AND ASSETS:

- **Flexible**
- **Knot resistance for B C E finishes**
- **Thin wall**
- **Lightweight**

TYPICAL APPLICATION:

- **Military**
- **Aeronautical**
- **Telecom**

**DESIGNATION:**

Flat braided tape made from continuous filament of high tenacity Polyester

SPEC.:

A-A-52081 (Formerly, MIL-T-43435 Type II)

NSA 8420-8 (LTTE4-O-E)

TEMPERATURE:

-67°C to 177°C (-100°F to 350°F)

COLOUR:

Natural (white) or Black. Other colors on request..

PACKAGING:

Size 1 & 2, rolls of 250 m

Size 3,4 & 5, rolls of 500 m

Part Number	Spec. Size	Width (mm)		Thickness (mm)		Strength (min.) (Kg)	Standard rolls (m)
		Min.	Max	Min.	Max		
LTTE1	1	4,57	5,59	0,33	0,48	61,2	250
LTTE2	2	2,51	3,07	0,30	0,46	36,3	250
LTTE3	3	1,96	2,39	0,28	0,43	22,7	500
LTTE4	4	1,37	1,68	0,23	0,38	11,3	500
LTTE5	5	1,14	1,40	0,15	0,36	6,8	500

FINISH:

- A Natural (uncoated)
- B Microcrystalline Fungicide Wax
- C Synthetic Elastomer Rubber
- E Vinyl Chloride or vinyl chloride acetate copolymer

ORDERING CODE:

ex: LTTE4-9-B (Size 4, White, finish B)

